



TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

NC Putty Grey

Properties

- It has a good filling and hiding property because of which it makes the surface desirable for refinishing.
- It has good flexibility and bending power.
- It has good water repellence.
- It also adheres to surface with great strength.
- It is soft cutting and so levelling can be achieved easily.

Application

Auto refinishes, wood, metals, etc.

Appearance

Butter like; easily spread able, smooth and grey in colour.

Benefits

- Higher solid contents keep the surface smoother.
- Soft cutting and easily sand able.
- High solid contents make it less sagging.
- Good covering.

Method of application

- All surfaces to be painted should be clean from wax, loose or flake coatings, dirt, rust, grease, etc.
- Clean it with Sand Paper or Thinner.
- Apply **TARALAC** "Red Oxide" or "Auto Oil Primer Brown" and let the surface dry.
- Apply **TARALAC** "NC Putty" to fill the dents and make the surface smooth. To make it more smoother and leveled use sanding paper.
- For bigger dents over coats can be applied.
- NC Putty is applied using flexible putty knife available in market.

Safety Information

Fire Hazard Class	Flammable
Safety Precaution	Wear Protective clothing like overalls, gloves and goggles
Storage	Store in a cool and dry place
Disposal	Dispose in land filling. Do not dispose in any drain or water channel.

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information

TDS Ver.No.: 0101.01/03102016