



# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com, Website: www.taralac.com

## DFU - NC PS Grey/White/Black

### Introduction:

Function of primer surface is to even out all minor surface defects, still left on the primed and puttied surface of a vehicle. It should have an ideal balance between the binder and the pigment/extenders that it can achieve evenness on a surface and also can offer a non-absorbent finish so that subsequent coat of a finishing paint does not penetrate its film, thereby losing gloss.

### Physicals constants:

Color	: Pleasing Grey
Finish	: Smooth & Silky just like butter
Wt. Per Lt	: Nearly 1.21 Kgs
Viscosity at 30 <sup>0</sup> C	: 25 Sec by ford cup No.4 when thinned with Butyl Acetate 1:1 by volume
Flexibility	: Passed 3 mm bending on bending mandrel.
Sanding	: Can be easily rubbed down to yield smooth & silky surface.

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information