



TARA PAINTS & CHEMICALS

Factory: A-423/14, Mahagujarat Ind.Estate, Sarkhej-Bavla Rd, Moraiya,
Dist-Ahmedabad, GUJARAT – 382210

Tel: (F): 02717-251256, 320003

Fax: 02717-251256

E-mail: taralac@hotmail.com

WEB: www.taralac.com

Taralac Clear Lacquer & Shades

Products Group : Nitrocellulose Base Paint

Items : NC Sanding sealer, NC Clear

	<ul style="list-style-type: none"> Taralac Ind.Lacquer Clear/Sanding Sealer is extensively used for polishing of wooden furniture, Anticorrosive metal coating & various industrial uses It has a good leveling as well as filling property & it offers good adhesion to wood & other substrate. It's clear lacquer is a clear liquid & highly viscous, non hazy & pale yellow, thereby maintaining the natural looks of the wood Taralac Ind. Clear Lacquer/Sealer is a high quality, quick drying clear lacquer. It is recommended for interior wooden furniture & Metal finishes. You can use Taralac Ind. Lacquer Clear/Sanding Sealer to get a Glossy, Matt or Satin finish.
Areas of Application	Metal, Interior Wooden Furniture & as a binder for various product, testing of pigments, Wooden Polish, Nail Polish, Glass Panting, Auto Refinishing etc.
Method of Application	Spray or cloth rag
Spray Viscosity	18-20 sec. On Ford Cup B4 at 30°C at a pressure of 30-40 p.s.i. (2.2 to 2.8 kg / cm ²)
Recommended Thinner	Solvent Mix 555 or Solvent Mix 211
Covering Capacity	20-24 sq. mt. / liter per coat (85-100 sq. ft) on non pours surface such as glass or Metal depending on application and film thickness & nature of wood in case of wood.
Number of Coats	Can be recoated multiple times.
Drying time at 30°C	Touch dry 5 - 10 minutes Sanding dry 3 to 4 hours Hard dry – overnight
Recoating time	0.5 to 2 hours at 30°C for sanding sealer 2 to 4 hours at 30°C for Clear Glossy / Matt
Flash Point	Below 5 °C
Finishes	Glossy, Matt or Satin (Smooth & Shiny surface)
Packing	200 ml, 500 ml, 1 lt, 4 lt, 20 lt, 200 lt

Note: NC Sanding sealer, NC Clear does not contain **LEAD OR CHROMATE** & certificate can be provided on request.