



TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

TARALAC MATT BLACK

Taralac MATT BLACK is extensively used for painting of wooden, Asbestoses, for Metals & as primer's. It is characterized by as good levelling property. It offers good resistance towards slippage of chalk during writing.

TECHNICAL DATA

Areas of application	Wood, Asbestoses, masonry, Metal etc.
Thinner recommended	Taralac St Thinner ST – 2
Method of application	Brushing or Spraying
Drying time	Surface dry - less than 30 minutes. Hard dry - less than 18 hours
Finish	Smooth and Matt
Covering capacity (spreading by brushing on smooth non absorbent surface)	20 - 24 sq. Mts./ltr/coat depending upon the nature of substrate at 20 - 25 microns film thickness
Gloss Level	15 – 25 at 60 ⁰ angle of gloss meter
Flash Point	Above 30 ⁰ C (86 ⁰ F)
Shade Available	Black
Packing Available	20 ltrs., 4 ltrs., 1 ltrs., 500 ml., 200 ml.,

Directions for use :

Ensure that the surface to be painted is free from loose matter, dust etc.

Two coats of black board paints is to applied so to get a better finish.

Taralac Matt Black May also be used as Synthetic Black Primer.

Apply a coat of paint by brushing after adjusting consistency using the recommended thinner. It can also be applied by spray applications.

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information

TDS Ver.No.: 1406.01/03102016