



# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

## BE ENAMEL PAINT

Taralac Enamel Paint is extensively used for painting of Barrels, Drums, wooden, Asbestos, Metals & as primer's. It is characterized by as good leveling property.

- Can be directly applied on pre-treated MS barrels and drums
- Suitable for multiple band application
- Easy application by hot spray or conventional spray
- Excellent gloss and opacity

### TECHNICAL DATA

Areas of application	Wood, Asbestos, masonry, Metal etc.
Thinner recommended	Taralac St Thinner ST – 2
Method of application	Brushing or Spraying
Drying time	Surface dry – 1 – 2 hr Hard dry - less than 18 hours
Viscosity	45 – 55 sec
Volume Solids	30 – 45%
Specific Gravity	0.85 – 1.15 kg/ltr
Finish	Smooth and Glossy
Covering capacity (spreading by brushing on smooth non absorbent surface)	18 - 24 sq. Mts./ltr/coat depending upon the nature of substrate at 20 - 25 microns film thickness
Flash Point	Above 30 <sup>0</sup> C (86 <sup>0</sup> F)
Shade Available	Various
Packing Available	20 ltrs., 4 ltrs., 1 ltrs., 500 ml., 200 ml.,

Directions for use:

Ensure that the surface to be painted is free from loose matter, dust etc.

Apply a coat of paint by brushing after adjusting consistency using the recommended thinner. It can also be applied by spray applications.

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information

TDS Ver.No.: 1450.01/15102014