



**TARALAC®**

# TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,  
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

## TARALAC LACCOLITE BLACK

**Introduction:** A hard coating compared to Rubber Coat, Chasis Black & Anti corrosive black

An anticorrosive & waterproofing paint, composed of bitumen, volatile organic solvent & special minerals, & specialised resins is considered having one of the best, cheapest & easy applicability. It is required for the following properties

- Anticorrosive properties.
- Acid & Alkali Resistance
- Termite resistance
- High adhesion to any kind of substrate.

### TECHNICAL DATA

<b>Uses</b>	Metal, Masonry & Wood etc.
<b>Thinner</b>	Taralac Syn. Thinner ST - 2
<b>Method of application</b>	Brushing, Spraying or dipping
<b>Sp.Gr. at 27° C</b>	0.90 to 1.0
<b>Covering capacity</b>	10 - 14 sq. Mts./lt/coat depending on the porosity of the surface and
(Spreading by brushing on smooth Non absorbent surface)	Upon the nature of substrate at 20 - 25 microns film thickness on non-adsorbent surface
<b>Flash Point</b>	Above 60° C
<b>Shade Available</b>	Black
<b>Packing Available</b>	200lt, 20lt, 4lt, 1lt, 500 ml, 200 ml.
<b>Ductility at 27° C</b>	2 or more than 2
<b>Areas of Application</b>	<ul style="list-style-type: none"><li>• As road marking paint</li><li>• On TMT bars used for construction</li><li>• For waterproofing, Damp Proofing, Mastic asphalt for roads &amp; floors, Foam Concreting. On terrace floors or to fill cracks.</li><li>• On any metal surface (pipes, bars, etc.)</li><li>• On old painted surfaces.</li><li>• Over brick masonry &amp; Concrete.</li><li>• Thick Coat As a Sound Proofing</li><li>• Before wooden Paneling</li></ul>

### Directions for use

Ensure that the surface to be painted is free from loose matter, dust etc.

Apply a coat of paint by brushing after adjusting consistency using the recommended thinner. It can also be applied by spray applications.

(The information in this leaflet is given in good faith but without warranty. Covering capacity is indicated on the Basis of results obtained on a prepared smooth surface.)

### Note

The container should be stored in tight lid, under the shed.  
Should not be exposed to naked flames.

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information

TDS Ver.No.: 2204.01/03102016