



TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade,
Village : Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com , taralac@taralac.com Website: www.taralac.com

SOLVENT BASED (NON - ACIDIC / ALKALI) PAINT REMOVER

For removal old alkyd paints, some types of epoxy, Vinyl, NC and polyurethanes. Paint Remover is a integral Part of many metal cleaning operations. TARALAC paint remover is a cold strip, Non-Acidic Non-Alkali & Neutral.

Characteristics and Physical Properties:

Appearance	Homogenous Liquid
Density approx	0.98 g / cm ³
Softening time approx	15 minutes (faster at higher temperature.)
Solid Content	5 – 6 %
Flash Point	20 - 25°C
Viscosity	16 – 18 sec

Recommended substrate Condition

Remove first loose paint layers by scraping.

System Specification:

- Apply a suitable quantity by soft haired brush.
- Thinner coats must be used on vertical work
- Use a soft haired brush.

Removal Procedure:

- Brush PAINT REMOVER in a quantity related to the thickness of the paint film that has to be removed.
- Wait between 5 and 10 minutes; remove with a paint scraper or filling knife the softened paint before it dries.
- Repeat this process in case of a very thick (old) paint film until all coats are removed.
- After drying, sand the surface and remove the remainder of the PAINT REMOVER with a brush, thereafter flush with water.

Precautions:

- Do not shake the tin. Puncture the lid before unscrewing, with a small nail wrapped in cloth to release the pressure. Try to avoid contact with skin, the softener in the PAINT REMOVER can burn the skin and is very volatile and dangerous if splashed onto skin, eye etc.
- If material has been in contact with the skin, flush with plenty of water and seek medical advise as soon as possible. This product should be used in well-ventilated areas. Al though this product is non-flammable smoking is prohibited during application and for a short time afterwards.

Physiological Hazards:

PAINT REMOVER does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. PAINT REMOVER is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.