



TARALAC®

TARA PAINTS & CHEMICALS

A/423/14, MAHAGUJARAT INDUSTRIAL ESTATE, SARKHEJ-BAVLA ROAD, B/H. SARVOTTAM HOTEL LANE, VILLAGE-MORAIYA, AHMEDABAD - 382210

Tel: (F): 02717- 320003

E-mail: taralac@hotmail.com

WEBSITE: www.taralac.com

An ISO 9001:2008 Certified Company

EPOXY TILE GROUT

Epoxy tile grout is a solvent free liquid epoxy based Resin & Hardener, comprising of a coloured liquid resin as Part A & liquid hardener. It is a two component product which durable, hygienic and chemically resistant. Epoxy base tile grout with ease of application and water wet able clean off properties.

ADVANTAGES:

1. It is tough and excellent bounding strength.
2. It is water and chemical resistant.
3. Resistance to thermal Expansion
4. Resistant to Bio Growth.
5. FDA & WARS approved
6. Meets food hygiene regulation
7. High resistant to wear and tear.
8. Suitable for grouting joints up to 20mm width.
9. Shrink Free
10. Aesthetic look

USES:

1. Suitable for Ceramics tiles, Mosaics, Terrazzo, quarry and natural stone tiles, vitrified.
2. Mosaics in interior and exterior installation
3. Tile joints in swimming pools.
4. Tile joints Airports, Industries, residence & commercial Complex etc where there is constant stress due to heavy traffic

POT LIFE	:	45 Minutes
SHELF LIFE	:	2 Year
CLEANING SOLVENT	:	Taralac Epoxy Thinner
MIXING RATIO	:	2 : 1

APPLICATION :

Mix thoroughly Part A & Part B in their respective containers before mixing. Add Part B to Part A & mix with gauging trowel. Gradually add the required amount of powder filler & mix until all the filler has been dispersed & homogenous colour is achieved. The Grout is mixed to a smooth, creamy consistency and applied with trowel or putty knife. Clean off surplus grout within 30 minutes of application with sponge soaked in clean water.

COVERAGE:

The coverage will depend on tile size and joint width. 6''x 6'' tile and 8mm Width –approx 1.5 kg per m²