

0101 NC Putty Grey

PROPERTIES

- It has a good filling and hiding property because of which it makes the surface desirable for refinishing.
- It has good flexibility and bending power.
- It has good water repellence.
- It also adheres to surface with great strength.
- It is soft cutting and so levelling can be achieved easily.

APPLICATION

Auto refinishes, wood, metals, etc.

APPEARANCE

Butter like; easily spread able, smooth and grey in colour.

BENEFITS

- Higher solid contents keep the surface smoother.
- Soft cutting and easily sand able.
- High solid contents make it less sagging.
- Good covering.

METHOD OF APPLICATION

- All surfaces to be painted should be clean from wax, loose or flake coatings, dirt, rust, grease, etc.
- Clean it with Sand Paper or Thinner.
- Apply TARALAC "Red Oxide" or "Auto Oil Primer Brown" and let the surface dry.
- Apply TARALAC "NC Putty" to fill the dents and make the surface smooth. To make it more smoother and leveled use sanding paper.
- For bigger dents over coats can be applied.
- NC Putty is applied using flexible putty knife available in market.

SAFETY INFORMATION

Fire Hazard Class	Flammable
Safety Precaution	Wear Protective clothing like overalls, gloves and goggles
Storage	Store in a cool and dry place
Shelf life	24 Months from the date of manufacturing
Disposal	Dispose in land filling. Do not dispose in any drain or water channel.