

## TARA PAINTS & CHEMICALS

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade, Village: Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com, taralac@taralac.com Website: www.taralac.com

## 0551 Silkwood Clear

Products Group: Single Pack Polyurethane

Items: Silkwood Clear

SILKWOOD VARNISH is a clear gloss varnish based on modified alkyd resin developed for **interior** & **Exterior** wooden surfaces. It has a good colour retention, weather resistance, easy to apply and durable finish.

		Ideal for all types of woods, hardwoods, joinery,
Areas of Application		clipboards. It can also be used on untreated wood and
		previously treated woods. For exterior.
Colour		Clear and Tinted
Viscosity		65 - 75 sec. On Ford Cup B4 at 30° C
% NVM		$45 \pm 2$
Method of Application		By brush or Spray
Method of Application		T
Spray Application Viscosity		18-20 sec. On Ford Cup B4 at 30°C at a pressure of
	101/	30-40 p.s.i. (2.2 to 2.8 kg / cm <sup>2</sup> )
	11	
<b>Recommended Thinner</b>		Thinner # 555, 111, ST2
Covering Capacity		14 - 16 sq. mt. / liter per coat on non pours surface
		such as glass or Metal depending on application and
	- Yeak	film thickness & nature of wood in case of wood.
	N/Z	The state of the s
Number of Coats		Can be recoated multiple times.
Number of Coats		
Finishes TAR/		Glossy & Matt Finish
		TLAC
Packing		200 ml, 500 ml, 1 lt, 4 lt, 20 lt
Packing		

## **Surface Preparation:**

- Surface must be clean, dry, and free from dirt, oil, grease and other foreign matters. If detergent is used for cleaning, rinse with fresh water.
- The temperature of the substrate should be min 50 C, above the dew point.

All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information

PDS Ver.No.: 0551.01/12112021



## **TARA PAINTS & CHEMICALS**

(An ISO 9001:2015 Certified Company)

A - 423 / 14, Mahagujarat Industrial Estate, Sarkhej - Bavla Road, Lane Behind Satyam Arcade, Village: Moraiya, Ahmedabad - 382 210, Gujarat (India)

Tel: (F): +91 8000011774, E-mail: taralac@hotmail.com, taralac@taralac.com Website: www.taralac.com



All the information given here are as per the results obtained in laboratory & are given in good faith to guide the user but without any warranty, the actual application results might vary depending on the conditions. We are not responsible for any loss, injury or damage resulting from the use of this information

PDS Ver.No.: 0551.01/12112021